

# SEFAR PET 1500

The screen printing mesh professionals use

SEFAR PET 1500 is the popular mesh for virtually every screen printing application – large and small-format graphics, CDs, decorative tile designs, printed glass, sporting goods, textile printing, and other industrial tasks.



## Mesh Features

SEFAR PET 1500 the most comprehensive range of screen printing mesh for an efficient and reproducible stencil production. It meets all the requirements for detail reproduction, homogeneity of face printing, print run consistency and registration accuracy in multi-color printing. The special SEFAR PET 1500 surface treatment aims to improve adhesion, good wettability and good antistatic properties. These features allow a high quality and efficient processing of all commercially available screen printing systems.

- Unsurpassed UV-light undercutting protection of yellow mesh
- Adhesion and preparation optimized mesh surface
- Reproducible mesh relaxation
- Good ink and paste release behaviour
- Good antistatic behavior thanks to Sefar antistatic treatment
- Wide standard range with high availability

## DOWNLOADS

[SEFAR PET 1500 Leaflet \(PDF 193 kb\)](#)

[SEFAR PET 1500 Article list \(PDF 879 kb\)](#)

[SEFAR PET 1500 Product data sheet \(PDF 238 kb\)](#)

## Sefar mesh selector app for smartphones

This app supports the screen printing user in selecting the optimal screen printing mesh depending on the application.

### Sefar Pty Ltd Filtration and Metal Mesh

19-21 Huntingwood Drive  
Huntingwood NSW 2148  
Australia

Phone +61 2 8822 1700  
Fax +61 2 8822 1744

[oceaniasales@sefar.com](mailto:oceaniasales@sefar.com)

[Go to content](#)



## Your Benefits

### Screen / stencil maker benefit

- Sharp-edged reproduction of the artwork on the stencil
- Finest detail reproduction
- Homogeneous coating
- Easy capillary film application
- The tension drop is stable and low
- Process and product reliability
- Adhesive passes good through the mesh, therefore less problem in bonding the mesh to the frame
- Reduced susceptibility of dust
- Reduction of retouching time
- Optimizing of storage management
- Short delivery time
- High reliability ensures continuous production

### Printer benefit

- High reproducibility
- Best edge definition in print
- Extended screen life
- High quality image reproduction
- Better color to color reproduction
- Good reproducibility of fine details
- Uniform ink application
- Maintaining of tightest color shade tolerances
- Error-free and clean printing
- Reduction of waste in the print process
- Ensured continual delivery of stencils
- Unlimited options of ink/paste film thickness

#### Sefar Pty Ltd Filtration and Metal Mesh

19-21 Huntingwood Drive  
Huntingwood NSW 2148  
Australia

Phone +61 2 8822 1700  
Fax +61 2 8822 1744

[oceaniasales@sefar.com](mailto:oceaniasales@sefar.com)

[Go to content](#)

## Applications

- Ceramics
- Electronics
- Glass
- Graphics
- Plastics and Packaging
- Textiles

SEFAR PET 1500 impresses with its performance in a wide variety of applications, ranging from graphic screen printing in small and large sizes, such as posters, displays, and signage; printing on plastics such as sporting goods, thermoformed parts, etc.; on the decoration of ceramic, directly or indirectly, and on up to textile printing and other industrial printing tasks.



Backlit posters with halftones higher than 30 lines/cm printed with SEFAR PET 1500



For selected clear varnish on labels, printed with SEFAR PET 1500



Great detail reproduction on ceramic decals (© Rosenthal) with SEFAR PET 1500

## Locations



### Sefar Pty Ltd Filtration and Metal Mesh

19-21 Huntingwood Drive  
Huntingwood NSW 2148  
Australia  
Phone: +61 2 8822 1700  
Fax: +61 2 8822 1744

■ E-Mail

### Sefar Pty Ltd Filtration and Metal Mesh

19-21 Huntingwood Drive  
Huntingwood NSW 2148  
Australia

Phone +61 2 8822 1700  
Fax +61 2 8822 1744

[oceaniasales@sefar.com](mailto:oceaniasales@sefar.com)

[Go to content](#)



**Sefar Pty Ltd**  
**Filtration and Metal Mesh**

Unit 4, 68 Callaway Street

Phone: +61 8 9303 2600

Fax: +61 8 6305 0930

■ E-Mail